

TECHNICAL DATA SHEET (TDS) SLUDGE PRESS



主要技术参数 / Main Technical Data

型号Model	ZDN05	ZDN10	ZDN15	ZDN20	ZDN25	ZDN30	ZDN35
带宽Belt Width (Mm)	500	1000	1500	2000	2500	3000	3500
电机功率Motor Power (Kw)	1.1	2.2	3	4	5.5	7.5	11
处理量 Process Capacity (M3/h)	0.5-4	3-6.5	4-9.5	5-13	7-15	8-20	12-30
洗网耗水量Water Consumption for Cleaning Fabric	3	3.5	5	8	10	15	17
洗网水压力Water Pressure For Cleaning Fabric	≥0.5	≥0.5	≥0.5	≥0.5	≥0.5	≥0.5	≥0.5
进浆浓度Inlet Consistency (%)	1-3	1-3	1-3	1-3	1-3	1-3	1-3
出浆浓度Outlet Consistency (%)	20-25	20-25	20-25	20-25	20-25	20-25	20-25

TECHNICAL DATA SHEET (TDS)

SLUDGE PRESS



主要技术参数 / Main Technical Data

螺旋直径screw diameter		φ500	φ650	φ750	φ900	φ1100	φ1250	φ1400
	型号Model	ZNV500N	ZNV650N	ZNV750N	ZNV900N	ZNV1100N	ZNV1200N	ZNV1400N
污泥浓度 sludge consistency	进泥浓度inlet consistency	15-22%	15-22%	15-22%	15-22%	15-22%	15-22%	15-22%
	出泥浓度outlet consistency	35-55%	35-55%	35-55%	35-55%	35-55%	35-55%	35-55%
产能Capacity (V24h)		2-8	10-20	15-30	20-40	35-50	40-65	55-85
装机容量功率Motor power (Kw)		5.5	11	15-18.5	22-30	30-45	55-90	75-110

依泥种, 要求不同, 产量有变动。如工艺要求低进泥浓度或更高出泥浓度, 参数可另行设计。

The Capacity shall be subject to type of sludge and requirements.

The machine can be in customized design if requested for lower inlet consistency or higher output consistency.